

# Symbol Explanations

Symbol	Meaning
	Article number
	Serial number
	Manufacturer
	Complies with Directive 93/42/EEC
	Distributor
	Unique Device Identification
	Single Patient – multiple use
	Applied part Type BF
	Water drop protected
	Keep away from sunlight
	Upper limit of temperature
	Atmospheric pressure limitation
	Contains or presence of natural rubber latex
	Contains phthalates
	Sterile
	Non-sterile
	This way up

Symbol	Meaning
	Order number
	Date of manufacture
	Authorized representative in the European Community / European Union
	Complies with Regulation (EU) 2017/745
	Customer number
	Consult instructions for use or consult electronic instructions for use
	Attention!
	Protection class II
	Protection against contact with fingers and medium-sized foreign bodies, protection against vertically falling water.
	Protect from heat and radioactive sources
	Lower limit of temperature
	Humidity limitation
	Contains no natural rubber latex
	Phthalate free
	Sterilised with ethylene oxide
	MR unsafe
	For food contact

Symbol	Meaning
	Batch code
	Use-by date
	Authorised representative in Switzerland
	Importer
	Medical Device
	Do not re-use
	Warning
	DC Voltage
	Do not use if package is damaged and consult instructions for use
	Keep dry / Store in a dry location
	Temperature limit
	Non-pyrogenic
	Fire, open sources of ignition and smoking prohibited
	Smoking prohibited
	Do not resterilize
	The device and its components may not be disposed of with normal commercial or household waste (batteries in particular)
	Fragile, handle with care






# Symbol Explanations






Symbol	Meaning
	Model number
	Patient identification
	Health care centre or doctor
	Sterilized using aseptic processing techniques
	Sterilized using vaporized hydrogen peroxide
	Double sterile barrier system
	Contains human blood or plasma derivatives
	Contains biological material of human origin
	Biological risks
	In vitro diagnostic
	Positive control
	Sampling site
	Liquid filter with pore size
	Prescription only
	.2: Nonflammable, non-toxic gases
	Postage
	Warning of explosive materials
	Quantity
	Maximum stacking load which may be stacked on the distribution packages






Symbol	Meaning
	Patient number
	Patient information website
	Date
	Sterilized using irradiation
	Sterile fluid path
	Single sterile barrier system with protective packaging inside
	Contains a medicinal substance
	Contains biological material of animal origin
	Protection against microorganisms
	Control
	Contains sufficient for <n> tests
	Fluid path
	One-way valve
	Translation
	5.1: Oxidizing substances
	Magnetic field
	Pacemaker
	Size
	Dead weight

Symbol	Meaning
	Patient name
	Country of manufacture
	Single patient use
	Sterilized using steam or dry heat
	Single sterile barrier system
	Single sterile barrier system with protective packaging outside
	Contains hazardous substances
	Contains nano materials
	Protection against bacteria and fungi
	Negative control
	For IVD performance evaluation only
	Drops per millilitre
	Protection against chemical risks (according to the requirements of EN 374-1:2003, 5.2.1)
	Repackaging
	Airfreight
	Warning of crushing of hands / Danger of crush injuries
	Handle with care
	max. load
	Recyclable product

# Symbol Explanations

Symbol	Meaning
	„ON“/“OFF“ (push/push)
	Status display state of charge
	Patient tube connection
High Vacuum / High Flow	High Vacuum / High Flow
	On Button
	No SpO <sub>2</sub> alarm
<b>A</b>	Tubus length
<b>CH</b>	Charrière
<b>Cuff Ø</b>	Standard cuff diameter
<b>O2-IN</b>	Oxygen inlet (connection for the O <sub>2</sub> source, spiral tube)

Symbol	Meaning
	Alternating current
	Adjusting direction to increase (+) and decrease (-) the vacuum
	Safe full level
	On (Power)
	Low Battery Display
<b>% SpO<sub>2</sub></b>	Partial oxygen saturation in percent
<b>A.D.   OD</b>	Outer diameter
<b>L</b>	Length
<b>Cuffed</b>	With cuff
<b>O2-OUT</b>	Oxygen outlet (connection for the O <sub>2</sub> nasal cannula)

Symbol	Meaning
	Status display power supply
	Vacuum connection
<b>Asp. MAX</b>	Maximum Vacuum
	Off (Power)
	Pulse rate (bpm)
	Temperature resistance
<b>I.D.</b>	Inner diameter
<b>Typ</b>	Type
<b>Uncuffed</b>	Without cuff